



## NEOTEC SKYRAILER

The Skyrailer 400RR offers a superb working envelope of **8.3m outreach** and **15.5m working height**, operating on a **200mm cant**. With a **360-degree basket capacity of 400kg**, the Skyrailer provides a **safe, stable elevated work platform for multiple operators**.

With the ability to navigate almost all ground conditions, the Skyrailer can **travel from the transport vehicle to on-tracking location** with ease. Fitted with **hydrostatic drive** the Skyrailer is suited for long-distance travel due to its advanced traction and braking system.

### Contact:

Sales@TXMPlant.co.uk  
01908 443000

WEIGHT:	12.5 T
WIDTH:	2500 mm
MAX REACH:	8.30 m
MAX WORKING HEIGHT:	15.50 m
BASKET CAPACITY:	400 kg (3 persons)
MAX ON/OFF TRACK CANT:	150 mm
MAX TRAVELLING CANT:	200 mm
MAX WORKING CANT:	200 mm
MAX GRADIENT:	1:25
TOWING CAPACITY:	1 T
ALO SPACEGUARD:	Y
TRAVEL UNDER LIVE OLE:	Y
PANTOGRAPH COMPATIBLE:	Y
ENGINE (EURO / kW):	EURO 3 / 34.1 kW

# TXMPlant

TXM Plant Ltd. Park Lane Industrial Estates,  
Ashton in Makerfield, Wigan. WN4 0BZ

[www.TXMPlant.co.uk](http://www.TXMPlant.co.uk)

#AsOneTXM